

UNCLASSIFIED

AD NUMBER	
AD346025	
CLASSIFICATION CHANGES	
TO:	unclassified
FROM:	restricted
LIMITATION CHANGES	
TO:	Approved for public release, distribution unlimited
FROM:	Controlling Organization: The British Embassy, 3100 Massachusetts Avenue, NW, Washington, DC 20001.
AUTHORITY	
DSTL, DSIR 23/31072, 16 Jul 2008; DSTDL, DSIR 23/31072, 16 Jul 2008	

THIS PAGE IS UNCLASSIFIED

CONFIDENTIAL
MODIFIED HANDLING AUTHORIZED

AD 346025

DEFENSE DOCUMENTATION CENTER

FOR

SCIENTIFIC AND TECHNICAL INFORMATION

CAMERON STATION, ALEXANDRIA, VIRGINIA



CONFIDENTIAL
MODIFIED HANDLING AUTHORIZED

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

NOTICE:

THIS DOCUMENT CONTAINS INFORMATION
AFFECTING THE NATIONAL DEFENSE OF
THE UNITED STATES WITHIN THE MEAN-
ING OF THE ESPIONAGE LAWS, TITLE 18,
U.S.C., SECTIONS 793 and 794. THE
TRANSMISSION OR THE REVELATION OF
ITS CONTENTS IN ANY MANNER TO AN
UNAUTHORIZED PERSON IS PROHIBITED
BY LAW.

346025

346025

CATALOGED BY DDC
AS AD No. _____

TECH. NOTE
STRUCTURES 336

U.S. CONFIDENTIAL - Modified Handling Authorized
RESTRICTED
U.S. RESTRICTED

TECH. NOTE
STRUCTURES 336

ROYAL AIRCRAFT ESTABLISHMENT
(FARNBOROUGH)

TECHNICAL NOTE No. STRUCTURES 336

**AN ANALYSIS OF FATIGUE
LOAD METER RECORDS FOR
LIGHTNING FAW Mks.I AND IA
AIRCRAFT IN R.A.F. SQUADRON USE**

U

by

F. W. Johnson, I.S.O., B.Sc.(Eng.) and Vera J. Pike, B.Sc.

1. THIS INFORMATION IS DISCLOSED ONLY FOR OFFICIAL USE BY THE RECIPIENT GOVERNMENT AND SUCH OF ITS CONTRACTORS, UNDER SEAL OF SECRECY, AS MAY BE ENGAGED ON A DEFENCE PROJECT. DISCLOSURE TO ANY OTHER GOVERNMENT OR RELEASE TO THE PRESS OR IN ANY OTHER WAY WOULD BE A BREACH OF THESE CONDITIONS.

JUNE, 1963

2. THE INFORMATION SHOULD BE SAFEGUARDED UNDER RULES DESIGNED TO GIVE THE SAME STANDARD OF SECURITY AS THAT MAINTAINED BY HER MAJESTY'S GOVERNMENT IN THE UNITED KINGDOM.

3. THE RECIPIENT IS WARNED THAT INFORMATION CONTAINED IN THIS DOCUMENT MAY BE SUBJECT TO PRIVATELY-OWNED RIGHTS.


MINISTRY OF AVIATION

THIS DOCUMENT IS THE PROPERTY OF H.M. GOVERNMENT AND ATTENTION IS CALLED TO THE PENALTIES ATTACHING TO ANY BREACH OF THE OFFICIAL SECRETS ACTS, 1911-1959

It is intended for the use of the recipient only, and for communication to such officers under him as may require to be acquainted with its contents in the course of their duties. The officers receiving this paper or communications are responsible that such information is reported with due caution and reserve. Any person other than the authorized holder, upon obtaining possession of this document, by finding or otherwise, should forward it, together with his name and address, in a closed envelope to:-

THE SECRETARY, MINISTRY OF AVIATION, LONDON, W.C.2

Letter postage need not be prepaid, other postage will be refunded. All persons are hereby warned that the unauthorized retention or destruction of this document is an offence against the Official Secrets Acts.

DDC
DEC 13 1963
TISIA D

RESTRICTED

U.S. CONFIDENTIAL - Modified Handling Authorized
U.S. RESTRICTED

EXCLUDED FROM AUTOMATIC
DECLASSIFICATION; DoD DIR 5200.10
DO NOT APPLY

U. S. CONFIDENTIAL
RESTRICTED
MODIFIED HANDLING AUTHORIZED

U.D.C. No. 533.6.048.1 : 620.178.3 [AI] (42) Lightning FAW Mk.1

Technical Note No. Structures 336

June, 1963

ROYAL AIRCRAFT ESTABLISHMENT

(FARNBOROUGH)

AN ANALYSIS OF FATIGUE LOAD METER RECORDS FOR
LIGHTNING FAW MKS.1 AND 1A AIRCRAFT IN R.A.F. SQUADRON USE

by

F. W. Johnson, I.S.O., B.Sc.(Eng.) and Vera J. Pike, B.Sc.

RAE Ref: Structures/E/16524

SUMMARY

Fatigue load meter records covering 4315 hours flying by 37 Lightning FAW Mks.1 or 1A aircraft in R.A.F. Squadron use up to February, 1962 have been analysed and load spectra have been drawn for six different types of flying and for all the flying combined. Comparison is made with the load spectrum from which the loading applied in a fatigue test on the wing was derived.

"This document contains information affecting the National Defense of the United States within the meaning of the Espionage Laws, Title 18, U.S.C., Sections 793 and 794. Its transmission or the revelation of its contents in any manner to an unauthorized person is prohibited by law."

U. S. CONFIDENTIAL
RESTRICTED

RESTRICTED

Technical Note No. Structures 336

LIST OF CONTENTS

	<u>Page</u>
1 INTRODUCTION	3
2 ANALYSIS OF RECORDS	3
3 LOAD SPECTRA	5
4 DISCUSSION OF RESULTS	5
5 SUMMARY OF RESULTS AND CONCLUSIONS	6
LIST OF REFERENCES	6
ADVANCE DISTRIBUTION	6
APPENDIX 1 - Lightning FAW 1 and 1A. Fatigue meter formulae for determining the percentage of wing life used	7
TABLES 1 - 4	8-11
ILLUSTRATIONS - Figs.1-4	-
DETACHABLE ABSTRACT CARDS	-

LIST OF TABLES

Table

1 - Amount of flying in each category	8
2 - Acceleration counts recorded in various categories of flying	9
3 - Relative damage rates and equivalent damage factors for various types of flying	10
4 - Acceleration frequencies for various types of flying	11

LIST OF ILLUSTRATIONS

Load spectrum for practice interceptions and similar duties	<u>Fig.</u> 1
Load spectra for (a) Initial familiarisation and air tests and (b) Conversion exercises and handling	2
Load spectra for (a) Formation flying, (b) Aerobatics and (c) Chase and gunfiring	3
Comparison between wing test spectrum and average load spectrum from fatigue meter records	4

MOD

RESTRICTED

Technical Note No. Structures 336

1 INTRODUCTION

Fatigue load meter records for Lightning FAW Mk.1 and 1A aircraft in R.A.F. Squadron use were examined to ascertain the frequencies of acceleration occurring in various types of flying and to enable an overall comparison to be made with the loading data adopted in 1959 for fatigue tests of the wing structure.

The records available, which were lent to the R.A.E. by the Air Ministry, covered the aircraft of three squadrons up to February, 1962. Recording began in No. 56 Squadron in January, 1961, in No. 74 Squadron in August, 1960 and in No. 111 Squadron in April, 1961. Thirty-seven aircraft were involved and the usable records covered a total of 4315 hours flying.

With very few exceptions the fatigue meter had been read after each flight and, by analysis of the records, it was possible to obtain a load spectrum for each type of flying in addition to an overall average load spectrum. Two types of fatigue meter were used, the Type 2D with six acceleration levels and the Type 14 with eight. It was assumed that the Lightning Mk.1 and 1A had the same flying characteristics and, therefore, that the results from each could be combined in the analysis.

2 ANALYSIS OF RECORDS

The fatigue meter records give the duration of each flight, the type of flying or duty carried out, the fatigue meter readings and certain other information not of interest for the present Note. Examination of the records showed that the flying could be divided into the following categories and the records were analysed to obtain the hours flown and the fatigue meter counts at the various 'g' levels in each category.

	<u>Category</u>	<u>Remarks</u>
1	P.I's	Practice interceptions, including scramble and cine camera exercises.
2	Radex	Radar exercises. It was subsequently ascertained that this type of sortie could be taken as being the same as a practice interception.
3	Navex	Navigation exercises with which have been included transit, ferry, practice diversion, reconnaissance and cross country flights.
4	Instrument approach	This includes GCA, ILS, TACAN, practice PAN (short for "panic") and let-downs.
5	Local	Local flying, not more explicitly defined; the amount is very small.
6	Target	One aircraft acting throughout the flight as a target for others.

- 3 -
U. S. CONFIDENTIAL
MODIFIED HANDLING AUTHORIZED

RESTRICTED

Technical Note No. Structures 336

	<u>Category</u>	<u>Remarks</u>
7	Initial familiarisation	This covers a limited amount of flying by the first squadron to receive the Lightning.
8	Air test	A flight test by the R.A.F. after maintenance or modification of the aircraft. Pre-delivery flight testing is not included since the records were not immediately available.
9	Convex	Conversion exercises and familiarisation other than that included in Category 7.
10	Handling	General flying on no particular defined duty.
11	Formation	All formation flying, including fly-pasts and displays.
12	Aeros.	Aerobatics and individual demonstrations.
13	Chase and gunfiring	Very small amounts of somewhat similar flying in each of these duties have been combined.

The amount of flying in each category in hours and as a percentage of the whole is shown in Table 1 for each squadron and for all three squadrons combined. The total counts for each type of fatigue meter in each category of flying are given in Table 2; these totals were obtained by adding the counts for all the aircraft in the three squadrons for the appropriate meter and category of flying. Rather more than half the total flying was recorded by the Type 2D meter. This flying occurred early in the period under review since the Type 2D meter was fitted first and was replaced by the Type 14 meter when supplies of the latter became available.

The basis chosen for comparing various types of flying was the fatigue damage rate for the most critical part of the wing structure as determined in the fatigue test. The damage rate would normally have been obtained from calculations based on the load spectrum and on stress-endurance information for the appropriate flight conditions but it was considered that, for the comparison required, sufficient accuracy would be obtained by use of the fatigue meter formulae. These formulae are provided by the aircraft manufacturer to enable the Service to ascertain from the meter readings the percentage of wing fatigue life used. Separate formulae are given for each type of meter and for different aircraft flying weights. These formulae, therefore, give a measure of the fatigue damage done and can be used to show the relative damage caused by the different types of flying.

For this analysis the formulae appropriate to a mean aircraft weight of 31,000 lb have been used for both Type 2D and Type 14 meters, (see Appendix 1). The relative damage rates obtained from these formulae are given in columns 2 and 3 in Table 3 for each type of flying. The two values were then combined in proportion to the amount of flying covered by each type of meter and the overall values are given in column 4. These values show broad similarities

of damage for some categories of flying and in order to simplify the analysis these have been combined in columns 5, 6 and 7 to give damage rates for six main groups of flying duties. Lastly in column 8 the overall relative damage rates have been reduced to equivalent damage rates by assuming a damage rate of unity for the group with the greatest number of flying hours. The percentage of flying time in each group is given in column 9.

3 LOAD SPECTRA

For the six groups of flying referred to above, the acceleration frequencies in counts per hour were calculated from the data in Table 2. These frequencies are given in Table 4 and are shown plotted in Figs.1 to 3 which give curves representing the combined results derived from the two types of fatigue meter. It will be noted that four g levels are common to both meters and for these the combined frequencies can be calculated; for other g levels the approximate combined frequencies were estimated and the values given in brackets in Table 4 were read from the resulting curves. The mean frequencies for all the flying combined, which are given at the bottom of Table 4 and shown plotted in Fig.4, were obtained by combining the mean frequencies for each group in proportion to the amount of flying done.

It should be noted that the load spectra for aerobatics and for chase and gunfiring (Fig.3) are based on relatively small amounts of flying and might possibly be altered when more records are available.

4 DISCUSSION OF RESULTS

The various groups of flying can be compared directly by means of the equivalent damage factors given in column (8) of Table 3, the factor for all the flying combined being 2.51. These factors show that some types of flying can be very severe from fatigue aspects; for example, one hour's flying on individual aerobatics gives the same expenditure of fatigue life as 29.3 hours flying on practice interceptions or similar duties. Formation flying has a particularly important influence on life usage because not only is the equivalent damage factor large (9.8) but the amount of flying is also large (nearly 12% of all flying).

From Fig.3 it will be observed that in both aerobatics and formation flying the frequency of counts at the 1.75 g level was less than expected from extrapolation of the upper curve of the load spectra. This probably arises from a design characteristic of the Type 14 meter¹ which does not record a count of 1.75 g until the acceleration, having reached or exceeded that value, is reduced slightly below 1 g. Thus under sustained acceleration such as in aerobatics or formation flying the 1.75 g level could be missed while higher levels which do not require a return to below 1 g are counted. This is shown on some records where the number of counts at 2.5 g is greater than those at 1.75 g. In a few isolated flights the number of 3.5 g counts exceeded the number of 2.5 g counts. From damage estimates using the fatigue meter formula, it was concluded that under-counting at the 1.75 g or 2.5 g levels to the extent so far observed has a very small effect on fatigue life and no adjustment of the formulae is necessary on this account.

RESTRICTED

Technical Note No. Structures 336

From Fig.4, in which the average fatigue meter load spectrum is compared with the wing test spectrum, it will be noted that high accelerations (i.e. 4 g and above) were applied less frequently and positive accelerations up to 3 g more frequently than allowed for in the test spectrum. Moreover, downward accelerations below 1 g occurred much more frequently than expected and this is undoubtedly due to the relatively large amount of formation and other low altitude flying recorded. At the time of the wing test, there was insufficient information available from Lightning fatigue meter records and the test loading, therefore, was based on Hunter and Javelin fatigue meter records, on Meteor V-g records and on standard gust data related to the Lightning interceptor sortie pattern. Despite this, the damage rate for all the service flying combined was only about 8% more than the damage rate estimated for the wing test load spectrum using the fatigue meter formula.

5 SUMMARY OF RESULTS AND CONCLUSIONS

(i) Load spectra have been obtained for various types of flying and these have been compared on the basis of fatigue damage as estimated by the fatigue meter formulae issued for monitoring wing life usage. Some types of flying, notably individual aerobatics and formation flying, can be very damaging compared with practice interceptions and similar duties. Formation flying has an important influence on fatigue life usage since this constituted nearly 12% of all flying in the period reviewed.

(ii) When the average load spectrum obtained from all the fatigue meter records was compared with the wing test spectrum, service flying was found to be 8% more damaging than the flying represented in the test. The difference is remarkably small having regard to the sources of information for the test load spectrum and the variety of flying carried out by Lightning aircraft.

LIST OF REFERENCES

<u>Ref. No.</u>	<u>Author</u>	<u>Title, etc.</u>
1	-	General Instruments - Accelerometers and fatigue meters. Air Publication 1275A, Volume 1, Section 12.

ATTACHED:-

Appendix 1
Tables 1 - 4

Figures 1 - 4 SME.88203/R - 88206/R
Detachable abstract cards

ADVANCED DISTRIBUTION:-

DCA (RD)	DACT	Director, RAE
DGAGS	D Mat	DDMAE (A)
DGSR(A)	AD/SRA	Aero Dept RAE
AD Structures (Action copy)	AD/AR	Naval Air Dept Bedford
D(RAF)A	AD/ADR	Library, RAE
D(RAF)B	TIL 170	Library, RAE Bedford 2
DPS	ARC/NPL Secretary	Pats.1/RAE
D(RN)A		

RESTRICTED

Technical Note No. Structures 336

APPENDIX 1

LIGHTNING FAW 1 AND 1A

FATIGUE METER FORMULAE FOR DETERMINING THE PERCENTAGE
OF WING LIFE USED

Type 2D meter (Mean aircraft weight = 31,000 lb)

$$\% \text{ life used} = \frac{1}{1000} (1.7h + 7.25A + 8.15B + 2.05C + 7.6D + 16E + 20F)$$

where h = number of hours flying in the period considered and A, B, C ... are the counts at acceleration levels of -1.5, -0.5, 2.5, 3.5, 4.5 and 6.0g respectively.

Type 14 meter (Mean aircraft weight = 31,000 lb)

$$\% \text{ life used} = \frac{1}{1000} (7.25A + 6.3B + 1.8C + 0.109D + 2E + 10F + 17G)$$

where A, B, C ... are the counts at acceleration levels of -1.5, -0.5, 0.25, 1.75, 2.5, 3.5 and 5.0 g respectively. Any counts at the 7.0 g level are ignored.

RESTRICTED

RESTRICTED

Technical Note No. Structures 336

TABLE 1Lightning FAW 1 and 1AAmount of flying in each category

Category of flying	No. 56 Sqn.		No. 74 Sqn.		No. 111 Sqn.		Total hours	% of grand total hours
	Hours	%	Hours	%	Hours	%		
1 P.Is.	82:55	6.7	793:05	46.3	109:20	8.0	985:20	22.85
2 Radex	726:45	59.0	0:45	0.05	779:40	56.9	1507:10	34.95
3 Navex	96:10	7.8	61:10	3.55	73:30	5.35	230:50	5.35
4 Instru- ment approach	12:05	1.0	66:00	3.85	70:05	5.1	148:10	3.45
5 Local	29:15	2.4	:50	0.05	11:50	0.85	41:55	0.95
6 Target	115:00	9.35	40:10	2.35	79:05	5.8	234:15	5.4
7 Initial familiar- isation	-	-	97:15	5.7	-	-	97:15	2.25
8 Air test	32:25	2.65	18:35	1.1	24:20	1.75	75:20	1.75
9 Convex	75:45	6.15	90:10	5.25	112:20	8.2	278:15	6.45
10 Handling	9:45	0.8	96:40	5.65	15:30	1.1	121:55	2.8
11 Formation	31:30	2.55	405:15	23.65	74:35	5.45	511:20	11.85
12 Aeros	17:20	1.4	29:00	1.7	7:25	0.55	53:45	1.25
13 Chase and gunfiring	2:50	0.2	13:30	0.8	13:05	0.95	29:25	0.7
Total hours	1231:45	-	1712:25	-	1370:45	-	4314:55	-

RESTRICTED

Technical Note No. Structures 336

TABLE 2
Lightning FM 1 and 1A
Acceleration counts recorded in various categories of flying

Category of flying	Counts at various acceleration levels and corresponding period of flying															
	Type 20 fatigue meter										Type 14 fatigue meter					
	g levels reached or exceeded						Period in hours	g levels reached or exceeded						Period in hours		
	-1.5	-0.5	2.5	3.5	4.5	6.0		-1.5	-0.5	0.25	1.75	2.5	3.5		5.0	7.0
1 P.I.s	1	23	1521	260	39	2	5:05:30	0	21	147	3383	977	206	8	0	339:50
2 Radar	0	11	1301	229	34	1	5:42:40	1	9	326	9240	2306	370	16	1	964:30
3 Hover	0	7	260	63	15	0	100:00	0	15	64	771	261	57	2	0	130:50
4 Instrument approach	3	16	176	32	1	0	8:30:00	0	7	31	434	136	23	1	0	66:10
5 Local	0	0	73	14	3	0	26:20	0	0	6	162	38	6	0	0	15:35
6 Target	0	1	199	55	9	0	10:55:55	0	2	44	762	287	49	0	0	128:20
7 Initial familiarization	0	9	779	133	14	0	97:15	-	-	-	-	-	-	-	-	-
8 Air test	2	30	147	36	5	1	35:05	2	10	56	518	216	59	3	0	40:15
9 Convex	0	16	774	136	8	0	23:45	0	3	41	514	210	30	2	0	44:30
10 Handling	0	10	243	53	9	0	86:05	1	3	22	353	121	34	5	0	36:50
11 Formation	18	148	11821	1563	242	8	34:30	0	8	492	5790	4242	572	29	0	168:00
12 Aeros	21	73	1719	493	211	26	33:00	8	47	127	797	693	277	55	0	20:45
13 Chase and gunfiring	0	0	59	5	1	0	17:15	0	0	3	210	84	34	2	0	12:10
Totals	45	344	19102	2672	591	38	2346:10	12	125	1359	22894	9571	1717	123	1	1965:45

RESTRICTED

TABLE 3
Lightning FAW 1 and 1A
Relative damage rates and equivalent damage factors for various types of flying

Category of flying (1)	Relative damage rates			Relative damage rates with certain categories combined			Equivalent damage factors with major role taken as unity (8)	Total flying in group as % of total flying in all groups (9)
	Type 2D meter (2)	Type 14 meter (3)	2D and 14 meter results combined (4)	Type 2D meter (5)	Type 14 meter (6)	2D and 14 meter results combined (7)		
1 P.I.s	1.09	1.45	1.21	1.13	1.13	1.13	1.0	72.95
2 Radar	1.10	1.06	1.08					
3 Navar	1.43	1.09	1.26					
4 Instrument approach	1.10	1.02	1.07	3.07	3.25	3.11	2.75	4.0
5 Local	1.32	1.05	1.22					
6 Target	1.09	0.96	1.02					
7 Initial familiarisation	3.16	-	3.16	1.42	2.08	1.55	1.37	9.25
8 Air test	2.83	3.25	3.05					
9 Convex	1.40	2.03	1.50					
10 Handling	1.48	2.15	1.68	11.8	9.68	11.1	9.8	11.85
11 Formation	11.8	9.68	11.1					
12 Aeros	36.5	27.8	33.1					
13 Chase and gunfiring	1.18	1.69	2.63	1.18	4.69	2.63	2.33	0.7

Note:- By adding the products of the last two columns and dividing by 100 a value of 2.51 is obtained for the equivalent damage factor for all the roles combined in the proportions given.

TABLE 4
Lightning FWH 1 and 1A
Acceleration frequencies for various types of flying

Type of flying	Counts per hour at the following g levels											Hours covered by records
	-1.5	-0.5	0.25	1.75	2.5	3.5	4.5	5.0	6.0	7.0		
Practice interceptions, etc.												
(a)	0.0027	0.039	-	-	2.35	0.434	0.067	-	0.002	-	-	1503:25
(b)	0.00061	0.033	0.376	8.97	2.44	0.432	-	0.016	-	0.00061	-	1644:15
(c)	0.0016	0.036	(0.375)	(8.97)	2.39	0.433	(0.067)	(0.023)	(0.002)	-	-	3147:40
Initial familiarisation and air tests												
(a)	0.015	0.295	-	-	7.00	1.28	0.144	-	0.0075	-	-	132:20
(b)	0.050	0.243	1.39	12.9	5.37	1.47	-	0.075	-	?	-	40:15
(c)	0.023	0.204	(2.77)	(20)	6.62	1.32	(0.20)	(0.075)	(0.0060)	-	-	172:35
Conversion exercises and handling												
(a)	0	0.081	-	-	3.18	0.591	0.053	-	0	-	-	319:50
(b)	0.012	0.075	0.784	10.8	4.12	0.797	-	0.087	-	0	-	80:20
(c)	0.0025	0.030	(0.8)	(10.8)	3.37	0.632	(0.08)	(0.025)	-	-	-	400:10
Formation												
(a)	0.052	0.431	-	-	34.4	3.97	0.705	-	0.023	-	-	343:20
(b)	0	0.048	2.93	34.2	25.2	3.40	-	0.473	-	0	-	168:00
(c)	0.035	0.305	(3)	?	31.4	3.78	(0.62)	(0.225)	(0.022)	-	-	511:20
Aerob												
(a)	0.636	2.21	-	-	53.0	14.9	6.39	-	0.788	-	-	33:00
(b)	0.366	2.27	6.12	38.4	33.4	13.3	-	2.65	-	0	-	20:45
(c)	0.540	2.23	(7.0)	?	45.4	14.3	(5.6)	(3.1)	(0.71)	-	-	53:45
Chase and gunfiring												
(a)	0	0	-	-	3.42	0.290	0.058	-	0	-	-	17:15
(b)	0	0	0.247	17.3	6.90	2.79	-	0.164	-	0	-	12:10
(c)	0	0	(0.237)	(17.3)	4.86	1.33	(0.25)	(0.08)	-	-	-	29:25
Mean of all types of flying	0.0132	0.109	(0.9)	?	6.64	1.06	(0.21)	(0.088)	(0.013)	?	?	4314:55

NOTE:- The values obtained from the Type 20 and 14 fatigue meter records are given at (a) and (b) respectively and the combined values are given at (c). The values in brackets were read from the curves in Fig 31 to 4.

FIG. 1




FIG. 1. LOAD SPECTRUM FOR PRACTICE INTERCEPTIONS & SIMILAR DUTIES.

FIG.2




FIG. 2. LOAD SPECTRA FOR (a) INITIAL FAMILIARISATION AND AIR TESTS
AND (b) CONVERSION EXERCISE AND HANDLING.

FIG. 3.




FIG. 3. LOAD SPECTRA FOR (a) FORMATION FLYING (b) AEROBATICS AND (c) CHASE AND GUNFIRING

LIGHTNING FAW. 18 1A




FIG. 4.

FIG. 4. COMPARISON BETWEEN WING TEST SPECTRUM AND AVERAGE LOAD SPECTRUM FROM FATIGUE METER RECORDS.

DETACHABLE ABSTRACT CARDS

These abstract cards are inserted in Reports and Technical Notes for the convenience of Librarians and others who need to maintain an Information Index.

Detached cards are subject to the same Security Regulations as the parent document, and a record of their location should be made on the inside of the back cover of the parent document.

<p align="center">RESTRICTED</p> <p>Technical Note No. Structures 336 Royal Aircraft Establishment</p> <p>533.6.048.1 : 620.178.3 [A1] (42) Lightning FAW Mk.1</p> <p>AN ANALYSIS OF FATIGUE LOAD METER RECORDS FOR LIGHTNING FAW Mk.1 AND 1A AIRCRAFT IN R.A.F. SQUADRON USE Johnson, F.W. and Pike, Vera J. June, 1963</p> <p>Fatigue load meter records covering 4315 hours flying by 37 Lightning FAW Mk.1 or 1A aircraft in R.A.F. Squadron use up to February, 1962 have been analyzed and load spectra have been drawn for six different types of flying and for all the flying combined. Comparison is made with the load spectrum from which the loading applied in a fatigue test on the wing was derived.</p>	<p align="center">RESTRICTED</p> <p>Technical Note No. Structures 336 Royal Aircraft Establishment</p> <p>533.6.048.1 : 620.178.3 [A1] (42) Lightning FAW Mk.1</p> <p>AN ANALYSIS OF FATIGUE LOAD METER RECORDS FOR LIGHTNING FAW Mk.1 AND 1A AIRCRAFT IN R.A.F. SQUADRON USE Johnson, F.W. and Pike, Vera J. June, 1963</p> <p>Fatigue load meter records covering 4315 hours flying by 37 Lightning FAW Mk.1 or 1A aircraft in R.A.F. Squadron use up to February, 1962 have been analyzed and load spectra have been drawn for six different types of flying and for all the flying combined. Comparison is made with the load spectrum from which the loading applied in a fatigue test on the wing was derived.</p>
<p align="center">RESTRICTED</p> <p>Technical Note No. Structures 336 Royal Aircraft Establishment</p> <p>533.6.048.1 : 620.178.3 [A1] (42) Lightning FAW Mk.1</p> <p>AN ANALYSIS OF FATIGUE LOAD METER RECORDS FOR LIGHTNING FAW Mk.1 AND 1A AIRCRAFT IN R.A.F. SQUADRON USE Johnson, F.W. and Pike, Vera J. June, 1963</p> <p>Fatigue load meter records covering 4315 hours flying by 37 Lightning FAW Mk.1 or 1A aircraft in R.A.F. Squadron use up to February, 1962 have been analyzed and load spectra have been drawn for six different types of flying and for all the flying combined. Comparison is made with the load spectrum from which the loading applied in a fatigue test on the wing was derived.</p>	<p align="center">RESTRICTED</p> <p>Technical Note No. Structures 336 Royal Aircraft Establishment</p> <p>533.6.048.1 : 620.178.3 [A1] (42) Lightning FAW Mk.1</p> <p>AN ANALYSIS OF FATIGUE LOAD METER RECORDS FOR LIGHTNING FAW Mk.1 AND 1A AIRCRAFT IN R.A.F. SQUADRON USE Johnson, F.W. and Pike, Vera J. June, 1963</p> <p>Fatigue load meter records covering 4315 hours flying by 37 Lightning FAW Mk.1 or 1A aircraft in R.A.F. Squadron use up to February, 1962 have been analyzed and load spectra have been drawn for six different types of flying and for all the flying combined. Comparison is made with the load spectrum from which the loading applied in a fatigue test on the wing was derived.</p>

CONFIDENTIAL
MODIFIED HANDLING AUTHORIZED

CONFIDENTIAL
MODIFIED HANDLING AUTHORIZED



*Information Centre
Knowledge Services*
[dstl] Porton Down,
Salisbury
Wiltshire
SP4 0JQ
22060-6218
Tel: 01980-613753
Fax 01980-613970

Defense Technical Information Center (DTIC)
8725 John J. Kingman Road, Suit 0944
Fort Belvoir, VA 22060-6218
U.S.A.

AD#: AD346025

Date of Search: 16 July 2008

Record Summary: DSIR 23/31072

Title: Analysis of Fatigue Load Meter Records for Lightning FAW (fighter all weather) Mk 1 and 1A Aircraft in RAF Squadron Use (RAE TN Structures 336)
Availability Open Document, Open Description, Normal Closure before FOI Act: 30 years
Former reference (Department) ARC 25235
Held by The National Archives, Kew

This document is now available at the National Archives, Kew, Surrey, United Kingdom.

DTIC has checked the National Archives Catalogue website (<http://www.nationalarchives.gov.uk>) and found the document is available and releasable to the public.

Access to UK public records is governed by statute, namely the Public Records Act, 1958, and the Public Records Act, 1967.

The document has been released under the 30 year rule.

(The vast majority of records selected for permanent preservation are made available to the public when they are 30 years old. This is commonly referred to as the 30 year rule and was established by the Public Records Act of 1967).

This document may be treated as UNLIMITED.